

CLAIMS AMENDMENTS

The present Listing of Claims replaces all prior versions, and listings, of claims. Compared to previous versions, claims 1, 6-7, 12, 17-18, 21, and 26-27 are amended. Claims 2, 8-11, 13, 19-20, 22, and 28-31 remain in original form. Claims 3-5, 14-16, and 23-25 are canceled without prejudice to their re-presentation in one or more child patent applications claiming priority to the present application.

Listing of Claims:

1 (currently amended). A linear actuator, comprising:

a housing;

a stop displaceable on a linear axis with respect to the housing;

at least one wire formed of a shape-memory alloy, said wire attached at a first end to the stop and at a second end to the housing for applying a pulling force to the stop when heated to a predetermined temperature to cause the stop to slide in a first direction into a housing interior channel;

a spring applying a biasing force to the stop in a second direction counter to the first direction; and

at least one jewel bearing defining a channel therethrough for slidingly receiving the wire and reducing frictional contact between the wire and the housing; and

a wire heater.

2 (original). The actuator of claim 1, wherein the housing further includes at least one curved wire guide.

3-5 (canceled).

6 (currently amended). The actuator of claim ~~[[5]]~~ 1, wherein the ~~bearing is a~~

jewel bearing is fabricated from any of the group consisting of ruby, sapphire, spinel, cubic zirconia, diamond, and any combination thereof.

7 (currently amended). The actuator of claim ~~[[3]]~~ 1, ~~wherein the means for reducing frictional contact is~~ further including a cylindrical shaft extending from the stop into the housing interior channel, the shaft defining a hollow interior adapted to receive the wire therethrough.

8 (original). The actuator of claim 7, wherein the shaft is fabricated from any of the group of materials consisting of stainless steel, aluminum, magnesium, titanium, carbon steel, copper, nickel, carbon-fiber composite, and any combination thereof.

9 (original). The actuator of claim 1, wherein the wire is fabricated from any of the group of shape memory alloys consisting of nickel-titanium, silver-cadmium, gold-cadmium, copper-aluminum-nickel, copper-tin, copper-zinc, copper-zinc-tin, copper-zinc-aluminum, copper-zinc-silica, indium-titanium, nickel-aluminum, iron-platinum, manganese-copper, iron-manganese-silica, and any combination thereof.

10 (original). The actuator of claim 1, wherein the means for heating the wire is an electrical source for applying an electrical current to the wire.

11 (original). The actuator of claim 1, wherein the housing includes cooperating slots and protrusions on an exterior surface thereof for connecting at least two actuators in parallel or in series.

12 (currently amended). An actuating device comprising:

at least two linear actuators configured in a parallel orientation, wherein each

actuator includes a housing having cooperating slots and protrusions on an exterior surface thereof for connecting the actuators, a stop displaceable on a linear axis with respect to the housing, at least one wire formed of a shape-memory alloy attached at a first end to the stop and at a second end to the housing for applying a pulling force to the stop when heated to a predetermined temperature to cause the stop to slide in a first direction into a housing interior channel, at least one jewel bearing defining a channel therethrough for slidingly receiving the wire and reducing frictional contact between the wire and the housing, and a spring applying a biasing force to the stop in a second direction counter to the first direction;

a plate adapted for concurrently attaching to each actuator stop; and

an electrical source for applying an electrical current to the wire of each actuator to cause the wire to heat to a predetermined temperature.

13 (original). The actuating device of claim 12, wherein each actuator housing further includes at least one curved wire guide.

14-16 (canceled).

17 (currently amended). The actuating device of claim ~~16~~ 12, wherein the ~~bearing~~ is a jewel bearing ~~is~~ fabricated from any of the group consisting of ruby, sapphire, spinel, cubic zirconia, diamond, and any combination thereof.

18 (currently amended). The actuating device of claim ~~14~~ 12, ~~wherein the means for reducing frictional contact is~~ further including a cylindrical shaft extending from the stop into the housing interior channel, the shaft defining a hollow interior adapted to receive the wire therethrough.

19 (original). The actuating device of claim 18, wherein the shaft is fabricated from

any of the group of materials consisting of stainless steel, aluminum, magnesium, titanium, carbon steel, copper, nickel, carbon-fiber composite, and any combination thereof.

20 (original). The actuating device of claim 12, wherein the wire is fabricated from any of the group of shape memory alloys consisting of nickel-titanium, silver-cadmium, gold-cadmium, copper-aluminum-nickel, copper-tin, copper-zinc, copper-zinc-tin, copper-zinc-aluminum, copper-zinc-silica, indium-titanium, nickel-aluminum, iron-platinum, manganese-copper, iron-manganese-silica, and any combination thereof.

21 (currently amended). An actuating device comprising:

at least two linear actuators configured in a serial orientation, wherein each actuator includes a housing defining an interior channel, a stop displaceable on a linear axis with respect to the housing, at least one wire formed of a shape-memory alloy attached at a first end to the stop and at a second end to the housing for applying a pulling force to the stop when heated to a predetermined temperature to cause the stop to slide in a first direction into the housing interior channel, at least one jewel bearing defining a channel therethrough for slidingly receiving the wire and reducing frictional contact between the wire and the housing, and a spring applying a biasing force to the stop in a second direction counter to the first direction;

an electrical source for applying an electrical current to heat the wire of each actuator to a predetermined temperature; and

a controller for causing the electrical source to apply current to predetermined individual applicator wires at predetermined timed intervals.

22 (original). The actuating device of claim 21, wherein each actuator housing further includes at least one curved wire guide.

23-25 (canceled).

26 (currently amended). The actuating device of claim ~~25~~ 21, wherein the ~~bearing~~
~~is a jewel bearing~~ is fabricated from any of the group consisting of ruby, sapphire, spinel,
cubic zirconia, diamond, and any combination thereof.

27 (currently amended). The actuating device of claim ~~23~~ 21, ~~wherein the means~~
~~for reducing frictional contact is~~ further including a cylindrical shaft extending from the stop
into the housing interior channel, the shaft defining a hollow interior adapted to receive the
wire therethrough.

28 (original). The actuating device of claim 27, wherein the shaft is fabricated from
any of the group of materials consisting of stainless steel, aluminum, magnesium, titanium,
carbon steel, copper, nickel, carbon-fiber composite, and any combination thereof.

29 (original). The actuating device of claim 21, wherein the wire is fabricated from
any of the group of shape memory alloys consisting of nickel-titanium, silver-cadmium, gold-
cadmium, copper-aluminum-nickel, copper-tin, copper-zinc, copper-zinc-tin, copper-zinc-
aluminum, copper-zinc-silica, indium-titanium, nickel-aluminum, iron-platinum, manganese-
copper, iron-manganese-silica, and any combination thereof.

30 (original). The actuating device of claim 21, further including a rotary dispenser,
the dispenser comprising:

- a bottom for receiving at least one vial for holding a substance to be dispensed;
- a dispensing nozzle;

- a central hub having a plurality of slots for receiving the actuator stops, thereby
preventing rotation of the dispenser;

means for rotating the dispenser when the stops are withdrawn from the central hub slots; and
a top.

31 (original). The actuating device of claim 30, wherein the means for rotating the dispenser is a coiled spring.